



TECHNICAL DATA SHEET

CMC TYPE	29065
-----------------	--------------

Excerpt from the technical data sheet of our supplier:

DESCRIPTION: GLASSINE SUPERCALENDERED KRAFT SILICONE COATED
ONE SIDED / SOLVENTLESS

COLOUR: WHITE

GRAMMAGE: (ISO 536)	62	+ 3	grs./m ²
		- 3	

CALIPER: (ISO 534)	55	+ 5	µm
		- 5	

TENSILE STRENGTH: (ISO 1924)	MD: (MIN)	5,30	kN/m
	CD: (MIN)	2,50	kN/m
TEARING: ELMENDORF (ISO 1974)	MD: (MIN)	260	mN
	CD: (MIN)	280	mN

MOISTURE: (ISO 287)	4,50	+ 1,50	%
		- 1,00	

RELEASE (FINAT-10 TESA TAPE 4651)	0,13	+ 0,05	N/25 mm
		- 0,05	

20 hrs at 23°C±2°C, 50% RH ±5%

under 70 gr/cm²

Speed: 300 mm/min

Angle: 180°

Data given above is for information only and therefore does not involve manufacturer warranty. Tests in production conditions should be carried out by users to confirm suitability of the paper.

Document may be subject to change without notice.

07/18