

TECHNICAL DATA SHEET

CMC TYPE	CMC 61144
Product description	Self adhesive insulating tape comprising excellent electrical properties and highest temperature performance in the group of polyester films. Available also in a version with increased adhesive thickness (CMC 61100).
Backing material	PEN film (polyethylene naphthalate)
Colour	colourless
Substrate thickness in mm	0.025
Total thickness in mm	0.040 ± 0.005
Adhesive properties	
Type of adhesive	acrylic
Adhesive strength in N/cm according to internal method PV 1006-32 (180° peel from steel)	≥ 3
Thermal properties	
Temperature performance (max.) in °C	155
Short term temperature performance in °C (ca. 1 hour)	200
Insulation class according to IEC 60085	F
Electrical properties	
Breakdown voltage based on IEC 60243-1 in V _{eff.}	≥ 5'500
Other properties	RoHS compliant ✓ REACH compliant ✓

Storage conditions: cool and dry (15 - 25°C, < 65% rel. humidity)

10/18

Quality guarantee: 12 months

The technical data are average values and subject to change without notice. They are not intended to replace user's testing.

Note on REACH: Some of our products do contain substances from the so-called candidate list. Please visit <https://en.cmc.de/page/reach> and check whether or not a purchased product is listed in our REACH statement and therefore does contain one or more SVHCs.