



preliminary TECHNICAL DATA SHEET

CMC TYPE	MP 8020-001C
Product description MP 8020-001C is double sided polyester tape with low adhesive strength on one side (clean removability from many surfaces) and permanently high adhesive strength on the other side (durable bonding). The adhesive side with low adhesive strength is covered with siliconized paper.	
Backing material	polyester (PET)
Colour	colourless
Substrate thickness in mm	ca. 0.012
Total thickness in mm	ca. 0.100
Adhesive properties	
Type of adhesive first side	modified acrylic adhesive
Adhesive strength first side after 1min in N/25mm (FINAT TM 1, on stainless steel, covered on one side with 0.05 mm PET)*	6
Type of adhesive second side	modified acrylic adhesive
Adhesive strength second side after 1min in N/25mm (FINAT TM 1, on stainless steel, covered on one side with 0.05 mm PET)*	16
Thermal properties	
Temperature resistance* (S.A.F.T.) in °C *	80
Other properties	 
Liner	siliconized paper

* average value

Storage conditions: cool and dry (15 - 25°C, < 65% rel. humidity)

01/22

Quality guarantee: 12 months

The technical data represents average values subject to change without notice. It is not intended to replace users' testing.

Note on REACH: Some of our products do contain substances from the so-called candidate list. Please visit <https://en.cmc.de/page/reach> and check whether or not a purchased product is listed in our REACH statement and therefore does contain one or more SVHCs.